


Anz.	Beschreibung
1	<p data-bbox="204 450 419 479">LIFTAWAY B120-2</p> <div data-bbox="316 517 475 801"></div> <p data-bbox="596 795 1050 819">Hinweis! Abbildung kann vom Produkt abweichen.</p> <p data-bbox="204 826 435 853">Produktnr.: auf Anfr.</p> <p data-bbox="204 889 1378 945">Grundfos LIFTAWAY is a collecting tank for grey wastewater designed according to EN 12050-2. The 120-litre tank can be equipped with two Grundfos UNILIFT KP.150/.250/.350 or UNILIFT CC5/7/9 pumps.</p> <p data-bbox="204 978 1378 1032">These products combined offer a compact lifting station for underfloor installation in basements to collect grey wastewater below sewer level and lift it up to the main sewer.</p> <p data-bbox="204 1037 1378 1090">The lifting station is suitable for pumping grey wastewater with a maximum particle size of 10-12 mm from, for example, washing machines, showers, washbasins or sinks.</p> <p data-bbox="204 1095 1043 1122">The lifting station must not pump wastewater containing discharge from toilets.</p> <p data-bbox="204 1155 1458 1209">The prefabricated corrosion-proof polyethylene tank has three DN 100 inlets, a DN 70 vent and cable entry, and an R 1 1/4" outlet.</p> <p data-bbox="204 1214 1372 1267">The tank cover has a floor drain with a siphon. You can use both sides of the cover. One side has an anti-slip surface; the other is prepared for paving tiles.</p> <p data-bbox="204 1272 1101 1299">The cover is placed on an extension neck to adjust the height to the basement floor.</p> <p data-bbox="204 1303 1442 1357">The pipe kit delivered with the tank includes a non-return flap valve and lever arm guide, which is to be clipped onto the pump for reliable start and stop.</p> <p data-bbox="204 1361 635 1388">The pumps must be ordered separately.</p> <p data-bbox="204 1393 1433 1447">The pumps must be without float switch, version M, and they must be connected to a pump controller, for example, LC 231.</p> <p data-bbox="204 1480 1449 1534">Note: A standard DN 400 PVC pipe can be used as additional tank extension. The tank comes with all internal pipes needed to connect the pump(s).</p>

Beschreibung	Daten
Allgemeine Informationen:	
Produktbezeichnung:	LIFTAWAY B120-2
Produktnummer:	auf Anfr.
EAN-Nummer:	auf Anfr.
Technische Daten:	
Zulassungen:	MORO, UKCA
Non-return valve type:	Flap valve
Anzahl Pumpen:	2
Werkstoffe:	
Behälter:	PLASTIC
Installation:	
Maximale Umgebungstemperatur:	40 °C
Inlet connection towards system:	DN 100
Outlet connection towards system:	BSPP1 1/4"
Fördermedium:	
Medientemperaturbereich:	5 .. 60 °C
Sonstiges:	
Nettogewicht:	18.2 kg
Bruttogewicht:	18.6 kg
Passend für folgende Produkte:	KP150/KP250/KP350/CC5/7/9
Herkunftsland:	DE
Zolltarif Nr.:	84137021

