

**Qty. Description**

1 Rigid suction lance w. level



Note! Product picture may differ from actual product

Product No.: On request

Rigid suction lance with adjustable length for mounting in a tank. They are installed at the lower end of the suction hose and consist of strainer (mesh size 0,8mm) non return valve, protective pipe and tank connection with entry holes for relief line and deaeration line

Additionally they include

- Reed-switch unit with two floaters for low level and empty indication (switch mode adjustable NO or NC)
- Cable with PE jacket
- M 12 plug to connect DDA, DDC, DDE or DDI dosing pump

Technical:

Max. Flow: 60 l/h  
Valve type: Low level and empty tank  
Pump connection: G5/8

Materials:

Basic: PE  
Valve ball: Ceramic  
Gasket: PTFE

Installation:

Type of connection: Hose  
Pipework connection: 4/6, 6/9, 6/12, 9/12  
Max immersion depth: 400 mm

Electrical data:

Length of cable: 5 m  
Type of cable plug: M12  
Plug type: Round

Others:

Country of origin: DE  
Custom tariff no.: 84818099



Company name:

Created by:

Phone:

Date:

20/01/2024

Description	Value
<b>General information:</b>	
Product name:	Rigid suction lance w. level
Product No:	On request
EAN number:	On request
<b>Technical:</b>	
Max. Flow:	60 l/h
Valve type:	Low level and empty tank
Pump connection:	G5/8
<b>Materials:</b>	
Basic:	PE
Valve ball:	Ceramic
Gasket:	PTFE
<b>Installation:</b>	
Type of connection:	Hose
Pipework connection:	4/6, 6/9, 6/12, 9/12
Max immersion depth:	400 mm
<b>Electrical data:</b>	
Length of cable:	5 m
Type of cable plug:	M12
Plug type:	Round
<b>Others:</b>	
Country of origin:	DE
Custom tariff no.:	84818099

