


Qty.	Description																												
1	<p><b>Rigid suction lance w. level</b></p>  <p><b>Note! Product picture may differ from actual product</b></p> <p>Product No.: On request</p> <p>Rigid suction lance with adjustable length for mounting in a tank. They are installed at the lower end of the suction hose and consist of strainer (mesh size 0,8mm) non return valve, protective pipe and tank connection with entry holes for relief line and deaeration line</p> <p>Additionally they include</p> <ul style="list-style-type: none"> <li>-Reed-switch unit with two floaters for low level and empty indication (switch mode adjustable NO or NC)</li> <li>-Cable with PE jacket</li> <li>-M 12 plug to connect DDA, DDC, DDE or DDI dosing pump</li> </ul> <p>Technical:</p> <table> <tr> <td>Max. Flow:</td><td>60 l/h</td></tr> <tr> <td>Valve type:</td><td>Low level and empty tank</td></tr> <tr> <td>Pump connection:</td><td>G5/8</td></tr> </table> <p>Materials:</p> <table> <tr> <td>Basic:</td><td>PE</td></tr> <tr> <td>Valve ball:</td><td>Ceramic</td></tr> <tr> <td>Gasket:</td><td>PTFE</td></tr> </table> <p>Installation:</p> <table> <tr> <td>Type of connection:</td><td>Hose</td></tr> <tr> <td>Pipework connection:</td><td>4/6, 6/9, 6/12, 9/12</td></tr> <tr> <td>Max immersion depth:</td><td>690 mm</td></tr> </table> <p>Electrical data:</p> <table> <tr> <td>Length of cable:</td><td>5 m</td></tr> <tr> <td>Type of cable plug:</td><td>M12</td></tr> <tr> <td>Plug type:</td><td>Round</td></tr> </table> <p>Others:</p> <table> <tr> <td>Country of origin:</td><td>DE</td></tr> <tr> <td>Custom tariff no.:</td><td>84818099</td></tr> </table>	Max. Flow:	60 l/h	Valve type:	Low level and empty tank	Pump connection:	G5/8	Basic:	PE	Valve ball:	Ceramic	Gasket:	PTFE	Type of connection:	Hose	Pipework connection:	4/6, 6/9, 6/12, 9/12	Max immersion depth:	690 mm	Length of cable:	5 m	Type of cable plug:	M12	Plug type:	Round	Country of origin:	DE	Custom tariff no.:	84818099
Max. Flow:	60 l/h																												
Valve type:	Low level and empty tank																												
Pump connection:	G5/8																												
Basic:	PE																												
Valve ball:	Ceramic																												
Gasket:	PTFE																												
Type of connection:	Hose																												
Pipework connection:	4/6, 6/9, 6/12, 9/12																												
Max immersion depth:	690 mm																												
Length of cable:	5 m																												
Type of cable plug:	M12																												
Plug type:	Round																												
Country of origin:	DE																												
Custom tariff no.:	84818099																												



Company name:

Created by:

Phone:

Date:

20/01/2024

Description	Value
<b>General information:</b>	
Product name:	Rigid suction lance w. level
Product No:	On request
EAN number:	On request
<b>Technical:</b>	
Max. Flow:	60 l/h
Valve type:	Low level and empty tank
Pump connection:	G5/8
<b>Materials:</b>	
Basic:	PE
Valve ball:	Ceramic
Gasket:	PTFE
<b>Installation:</b>	
Type of connection:	Hose
Pipework connection:	4/6, 6/9, 6/12, 9/12
Max immersion depth:	690 mm
<b>Electrical data:</b>	
Length of cable:	5 m
Type of cable plug:	M12
Plug type:	Round
<b>Others:</b>	
Country of origin:	DE
Custom tariff no.:	84818099

20/01/2024

### Order Data:

Position	Your pos.	Product name	Amount	Product No	Total
		Rigid suction lance w. level	1	On request	Price on request