

Qty. Description

1 Rigid suction lance w. level



Note! Product picture may differ from actual product

Product No.: On request

Rigid suction lance with adjustable length for mounting in a tank. They are installed at the lower end of the suction hose and consist of strainer (mesh size 0,8mm) non return valve, protective pipe and tank connection with entry holes for relief line and deaeration line

Additionally they include

- Reed-switch unit with two floaters for low level and empty indication (switch mode adjustable NO or NC)
- Cable with PE jacket
- M 12 plug to connect DDA, DDC, DDE or DDI dosing pump

Technical:

Max. Flow: 60 l/h
 Valve type: Low level and empty tank
 Pump connection: G5/8

Materials:

Basic: PE
 Valve ball: Ceramic
 Gasket: PTFE

Installation:

Type of connection: Hose
 Pipework connection: 4/6, 6/9, 6/12, 9/12
 Max immersion depth: 1100 mm

Electrical data:

Length of cable: 5 m
 Type of cable plug: M12
 Plug type: Round

Others:

Country of origin: DE
 Custom tariff no.: 84818099



Company name:

Created by:

Phone:

Date:

20/01/2024

Description	Value
General information:	
Product name:	Rigid suction lance w. level
Product No:	On request
EAN number:	On request
Technical:	
Max. Flow:	60 l/h
Valve type:	Low level and empty tank
Pump connection:	G5/8
Materials:	
Basic:	PE
Valve ball:	Ceramic
Gasket:	PTFE
Installation:	
Type of connection:	Hose
Pipework connection:	4/6, 6/9, 6/12, 9/12
Max immersion depth:	1100 mm
Electrical data:	
Length of cable:	5 m
Type of cable plug:	M12
Plug type:	Round
Others:	
Country of origin:	DE
Custom tariff no.:	84818099

