



- Hybrid (i.e. ESaver)
- Peak shaving (grid & generator)
- Island mode

Technical data *	
Service Object data	
Dimensions with frame	2438 x 1965 x 2525 mm (L x W x H)
Weight	3.700 kg
Specifications	
Nominal rate power	80 kW / kVA
Nominal capacity	89 kWh
Nominal usable energy	81 kWh
Nominal voltage range	360 – 440 V
Frequency	50 / 60 Hz
Nominal rated current (input / output)	115 / 240 A
Minimum charging power	8 kW
Charging time (32A / 63A / 80A)	268 / 134 / 107 min
System	
Average noise level (active)	< 60 dB (A)
Mains circuit (input)	1x set Power locks
Load circuit (output)	1x set Power locks
Operations	
Max energy (self)consumption	1,5 kWh
Others	
Certificates & Approvals	UN 38.3 IEC 62619 IEC 62477 IEC 62933-2-1 UL 1642 UL 1973 UL 9540A CE Declaration of Conformity VDE-AR-N 4105 EN-50549-1

* The data corresponds to the displayed article. Specifications of delivered article may different.

For other equipment visit our website:

Generators



Distribution



Cables



Would you like to know more about our products? We will be happy to help and advice you to find an individual power solution.